

IN THE SPECIFICATION:

Please replace the paragraph beginning at page 26, line 2, with the following rewritten paragraph:

Referring to ~~Fig. 5(c)~~ Fig. 5(d), in a fourth step after the injecting of the coating material (paint), the mold 10 is closed and clamped again by moving the moving mold 14 toward the fixed mold 12 to allow the coating material to spread and flow in the gap, thus coating the molded product with the coating material.

Please replace the table beginning at page 35, line 1, with the following rewritten table:

(Table 1)

Molded product thickness

Examples/ Comparative examples	Comparative Example 1	Comparative Example 2	Example 1	Example 2	Example 3	Comparative Example 3
Mold-clamping force in first step (ton)	850	850	850	850	850	850
Mold-clamping force in second step (ton)	850	400	300	200	100	50
Maximum thickness (mm)	3.262	3.186	3.257	3.240	3.243	-
Minimum thickness (mm)	3.050	2.988	3.141	3.154	3.164	-
Difference between maximum and minimum thicknesses	0.212	0.198	0.116	0.086	0.079	-
Average	3.15	3.11	3.20	3.21	3.21	-
Standard deviation	0.058	0.058	0.038	0.035	0.029	-
Surface condition	Good	Good	Good	Good	Good	Sink marks occurred